

Hawkeye[®] Pro Hardy Specifications

Optics

Field-of-View 50°

Direction-of-View 0°

Relay Optics e2 endoGRINs[®] Glass Relay Lenses

Magnification Borescopes are not fixed magnification like microscopes. See [chart](#).

Mechanical / Construction

Length 7", 12", 17", 22"

Diameter Scope: .250" (6.35 mm), w/ Mirror Tube: .313 (8.00 mm)

Lightpost LightConcentrator[™] ACMI configuration, Diameter 0.300"

Eyecup Standard DIN, 32 mm diameter, with independent focusing ring

Materials

Tube	304 Stainless Steel
All Machined Stainless Steel	303 Stainless Steel
Eyecup and Focusing Ring	Aluminum, black anodized
Front Window	AR coated optical Glass
Illumination Fiber	Optical Glass
Relay Optics	e2 endoGRINs® gradient index glass lenses

Environmental

Temperature Range	Official - 20° to 120° C.
Note 1	Hawkeye Pro Rigid Borescopes can be made to operate up to 300 deg. C on a custom Basis. Contact your sales representative for details.
Note 2	These scopes were not designed to operate below 0°. However, several of our customers have successfully used the scopes in liquid Nitrogen at 77 deg. K.

Pressure

All Hawkeye borescopes we designed only for use at ambient pressure, however, we have several customers who have successfully used Hawkeye Borescopes at pressures up to 500 PSI and down to 10⁻⁶ Torr. As the scopes were not specifically designed for this, the operator does so at his own risk.

Chemical Resistance

All Hawkeye Pro Rigid borescopes (tube only, not the eyepiece end) are water tight and are resistant to most hydrocarbons; oils, gasoline, hydraulic fluid, jet fuel, etc. Exposure to Acids and strong Alkali should be avoided as it will attack the optical window.